

Honeywell LP and LE Series Pressure Switches

Product Nomenclature

For example, a **LPR00550PFPVKAAA01** defines a low pressure switch, rising factory set, non-adjustable set point, 55 psi set point, psig, sealed gage pressure unit, M14 x 1.5 port type, SPST-NO gold-plated contacts output, stainless steel base, Kapton® diaphragm (Teflon® coated), Nitrile O-ring actuation/application, spade terminal connectors, standard switch, individually boxed units.

| LP | R | 00550 | P | F | P | V | K | AA | A | 01 |
|--|--|--|----------------------------|----------------------|---|--|---|---|---|--|
| Series | Set Point | Pressure Set Point | Pressure Unit | Port Type | Output | Base | Actuation/ Application | Connector Type | Options | Packaging Options |
| LP Series, LE Series Low Pressure Switch | R Rising factory set, non-adjustable | 0,24 bar to 10,34 bar [3.5 psi to 150 psi] | P psig, sealed gage | A 1/4-18 NPT | P SPST-NO, gold-plated contacts | B Brass | K Kapton diaphragm (Teflon coated), Nitrile O-ring ¹ | AA 1/4 in Spade Terminals | A Standard switch | 01 Individually boxed units |
| | F Falling factory set, non-adjustable | NOTE: Pressure set point is always five digits. For bar, the set point value will be multiplied by 100 and entered in the listing. For example, 15.45 Bar is noted as 01545. This allows for 2 decimal places. For psi, the set point value will be multiplied by 10 and entered in the listing. For example, 245.5 psi is noted as 02455. This allows for 1 decimal place. | B bar, sealed gage | B 1/8-27 NPT | M SPST-NC, gold-plated contacts | N Cold-rolled steel | H Kapton diaphragm (Teflon coated), EPDM O-ring ² | BA Screw Terminals | B With 3 shrink sleeve | 15 25 individual boxes packed in bulk packaging |
| | T Rising, field adjustable* | | M bar, true gage | C 1/2-20 UNF | Y SPDT-NO/NC, gold-plated contacts | V Stainless steel | T Tefzel diaphragm, Nitrile O-ring ³ | CA Deutsch DT04-3P-E005 (3-Pin Connector) | C With shrink sleeve (plastic coating) | 20 150 units in bulk packaging |
| | C Falling, field adjustable* | | T psig, true gage | D 1/8-27 PTF | | U Tefzel diaphragm, EPDM O-ring ⁴ | | DA Amp Super Seal 1.5 - 282105-1 (3-Pin Connector) | D With shrink sleeve (acrylic coating) | |
| * Field adjustable option is only available for: 1. Blade and screw terminations 2. Deutsch DT04-3P (SPDT, SPNO, SPNC) 3. Amp Superseal 1.5 (3-pin) (SPNO & SPNC) | | Blade and screw electrical terminations are available with only the true gage option. True gage option is available only up to 20 psig set point for integral connectors and wire out electrical terminations. | E M12 x 1.5 | F M14 x 1.5 | | ¹ Air, Petroleum-based hydraulic fluid, engine oil ² Glycol-based fluid ³ For high temperature fluid media ⁴ For high temperature fluid media, glycol-based fluid | EA 10-inch Cable, 18 AWG (Wire Out, No Connector) | E With 1/8 watt resistor between terms. | | |
| | | | G 9/16-18 UNF | H 3/4-16 UNF | | | FA 10-inch Cable w/Deutsch DT04-3P-E005 (3-Pin Connector) (16 AWG)* | F 304,8 mm [12 in] total wire length | | |
| | | | J G1/8 BSPP | M 7/16-20 UNF | | | GA 10-inch Cable w/Amp Super Seal 1.5 - 282105-1 (3-Pin Connector) (18 AWG)* | G With conduit sleeve | | |
| | | | R R1/8 BSPT | T M10 x 1.0 | | | HA 10-inch Cable w/Metripack 280 Delphi 15300002 (2-Pin Connector) (18 AWG)* | R With port neck o-ring | | |
| | | | T M10 x 1.0 | V R1/2 BSPT | | | JA 10-inch Cable w/Din43650-C (3-Pin Connector) (18 AWG)* | | | |
| | | | V R1/2 BSPT | Y G1/4 BSPP | | | KA 10-inch Cable w/M12x1 (Brad Harrison Micro) - 21032121306 Harting P/N (3-Pin Connector) (18 AWG)* | | | |
| | | | Y G1/4 BSPP | Z R1/4 BSPT | | | LA 10-inch Cable w/Packard Weatherpack Male Terminal - 12020827 (3-Pin Connector) (18 AWG) | | | |
| | | | Z R1/4 BSPT | | | | MA 10-inch Cable w/Deutsch DT04-2P-E005 (2-Pin Connector) (18 AWG) | | | |
| | | | | | | | NA 3-inch Cable w/Packard 2P Tower Connector - 12015792 (2-Pin Connector) (18 AWG) | | | |
| | | | | | | | PA 2.75-inch Cable w/Packard 2P Shroud Connector - 12010973 (2-Pin Connector) (18 AWG) | | | |
| | | | | | | | RA 4-inch Cable w/Packard 2P Shroud Connector - 12010973 (2-Pin Connector) (16 AWG) | | | |
| | | | | | | | SA 5.5-inch Cable w/ITT Cannon 2P Sure-Seal Circular Connector - SS2R-120-1804-000 (2-Pin Connector) (18 AWG) | | | |
| | | | | | | | TA 8.5-inch Cable w/ITT Cannon 3P Sure-Seal Circular Connector - SS3R-120-8551-001 (3-Pin Connector) (16 AWG)* | | | |
| | | | | | | | UA 10-inch Cable - Vacuum Impregnated w/Deutsch DT06-3S-E006 (3-socket Connector) (16 AWG)* | | | |
| | | | | | | | VA 10-inch Cable - Vacuum Impregnated w/Deutsch DT04-3P-E005 (3-Pin Connector) (16 AWG)* | | | |
| | | | | | | | WA 4.5-inch Cable w/ 1/4 in Spade Terminals 6,3 mm x 0,8 mm (16 AWG)* | | | |
| | | | | | | | YA 6-inch Cable w/Amp Super Seal 1.5 - 282104-1 (2-Pin Connector) (18 AWG)* | | | |
| | | | | | | | ZA 10-inch Cable w/Deutsch DT06-2S-CE06 (2-socket Connector) (18 AWG) | | | |
| | | | | | | | AB Deutsch DT04-2P-E005 (2-Pin Connector)** | | | |
| | | | | | | | BB 10-inch Cable w/Metripack 150 Delphi 12129615 (3-Pin Connector) (18 AWG)* | | | |
| | | | | | | | DB 10-inch Cable w/AMP 2,5 mm System Series Connector 1-967402-1 (18 AWG)* | | | |
| | | | | | | | EB 4.5-inch Cable w/Packard Shroud Connector 12015792 (2-Pin Connector) (18 AWG) | | | |
| | | | | | | | FB 10-inch Cable w/Metripack 150 Delphi 12052641 (2-Pin Connector) (18 AWG) | | | |
| | | | | | | | GB 10-inch Cable w/Deutsch Plug HD 16-3 96S (3-Pin Connector) (16 AWG)* | | | |

NOTE: Not all combinations of model code are available. Please contact your Honeywell provider/representative for assistance.



*These connectors are designed for dual circuit (SPDT) by default. They can be used for single-circuit applications (SPNC/SPNO) by making suitable connections. Refer to wiring diagram.
**Option AB is available only for LP and LE Series.